

# Tercet® 60" drop-in bath K-1161

### **Features**

- Spacious design accommodates up to two bathers.
- Molded lumbar supports and armrests offer extra comfort while bathing.

### Material

Acrylic

### Installation

Drop-in or corner alcove.

### **Additional Hydrotherapy Options**

- Soaking Bath 1161-0
- Whirlpool 1160-0
- Whirlpool + heater 1160-H

### **Recommended Products/Accessories**

K-1491 Bath/Whirlpool Pillow K-11677 Bath Drain K-1601 Bath/Whirlpool Footstop K-7213 27" Cable Bath Drain K-7214 27" Cable Bath Drain K-7259 Clearflo Bath Drain K-37382 45" Rough-in Cable Bath Drain



### Codes/Standards CSA B45.5/IAPMO Z124 UL 1795

# **KOHLER® Plastic Baths and Receptors Lifetime Limited Warranty**

See website for detailed warranty information.

### Available Colors/Finishes

Color tiles intended for reference only.

Color	Code	Description
	0	White
	96	Biscuit
	47	Almond





35"

(889 mm)

63"

60'

21'

(1524 mm)


(1600 mm)

(889 mm)

### **Tercet®**

## 60" drop-in bath K-1161

No change in measurements if connected with drain illustrated. (K-11677) **Recommended Faucet Location** 



29" (737 mm)

4-7/8"

1-1/2"

Bath Drain

13-1/8"

(333 mm)


(124 mm)

43-3/4"


(1111 mm)

2-7/8"

(73 mm)



Cut-Out Detail



### **Technical Information**

19-1/2"

(533 mm) (495 mm)

All product dimensions are nominal.

Installation: Drop-in Center Drain location:

Basin area, bottom: 52" x 38-3/4" (1321 mm x 984 mm) Basin area, top: 61" x 46-1/4" (1549 mm x 1175 mm)

(737 mm)

60" (1524 mm)

Weight: 91 lbs (41.3 kg)

Minimum floor load: 38 lbs/ft<sup>2</sup> (185.5 kg/m<sup>2</sup>)

Water depth: 15" (381 mm) Water capacity: 96 gal (363.4 L)

Cutout: Drop-in, 57-1/2" x 27-1/2" (1461 mm x

699 mm)

### **Notes**

Measure your actual product for rough-in details. Install this product according to the installation instructions.

The hot water supply should be 70% of the capacity of the bath or greater. Installations will

If installing a rim-mount faucet, make sure there is no interference above or below the deck before drilling any holes.

